# NSN 5970-01-226-6494

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-226-6494

T	m	nı	ırat	ure	Ra	tin	u.
15	71 I I	υu	ıιαι	uie	I\a		u.

-55.0 degrees celsius and 225.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

# Main Body Wall Thickness:

0.080 inches after unrestricted recovery

#### Main Bodylength:

3.900 inches after unrestricted recovery

# Main Body Small End Inside Diameter:

1.680 inches as supplied

#### Main Body Large End Inside Diameter:

1.680 inches as supplied

#### Distance From Bottom Of Shoulder To Large End Of Main Body:

2.470 inches after unrestricted recovery

#### Distance From Top Of Shoulder To Small End Of Main Body:

0.710 inches after unrestricted recovery

# Min. Tensile Strength (psi):

1500 pounds per square inch

#### **Special Features:**

Includes two molding ports 0.180 in. Diameter and 0.120 in. Dia; inside coated with s-1017 adhesive

# Flexibility:

Flexible

# Color:

Black

#### Material:

Plastic, polyolefin, rt-301, raychem corp

# Material:

Plastic, polyolefin, rt-301, raychem corp

# **Style Designator:**

Boot-straight

# **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# Shelf Life:

N/a

#### **Unit Of Measure:**

#### **Demilitarization:**

No

# Fiig:

A22500