# NSN 5970-01-226-9702

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-226-9702

# **Tempurature Rating:**

-55.0 degrees celsius and 225.0 degrees celsius

# Large End Wall Thickness Of Main Body:

0.130 inches after unrestricted recovery

#### Small End Wall Thickness Of Main Body:

0.130 inches after unrestricted recovery

## Distance From Intersecting Centerlines To Edge Of Small End:

3.070 inches after unrestricted recovery

# Distance From Centerline Of Small End To Edge Of Large End:

1.320 inches after unrestricted recovery

#### Main Body Small End Inside Diameter:

2.040 inches as supplied

#### Main Body Large End Inside Diameter:

2.040 inches as supplied

# Distance From Top Of Shoulder To Small End Of Main Body:

1.320 inches after unrestricted recovery

# Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

# Min. Tensile Strength (psi):

1500 pounds per square inch

# **Special Features:**

Coated with s-1017 adhesive; large end has lip

# Flexibility:

Semirigid

# Height:

2.080 inches after unrestricted recovery

# Color:

Black

# Material:

Plastic, polyolefin, rt-301, raychem corp

### Material:

Plastic, polyolefin, rt-301, raychem corp

# **Style Designator:**

Boot-90 degrees

# **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# Shelf Life:

N/a

# **Unit Of Measure:**

--

## **Demilitarization:**

No

# NSN 5970-01-226-9702

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500