Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-227-1109

view Online at https://aerobasegroup.com/nsn/5970-01-227-1109
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Wall Thickness:
0.060 inches after unrestricted recovery
Main Bodylength:
1.500 inches after unrestricted recovery
Main Body Small End Inside Diameter:
0.910 inches as supplied
Main Body Large End Inside Diameter:
0.910 inches as supplied
Distance From Bottom Of Shoulder To Large End Of Main Body:
0.860 inches after unrestricted recovery
Distance From Top Of Shoulder To Small End Of Main Body:
0.360 inches after unrestricted recovery
Min. Tensile Strength (psi):
1500 pounds per square inch
Special Features:
Includes tow molding ports; inside adhesive coated
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, 3m co
Style Designator:
Boot-straight
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A22500