Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-228-8339

| Reliabil  | ity Indicator:  |
|-----------|---|
| Not esta  | blished   |
| Overall   | Length:   |
| 1.750 in  | ches  |
| Tempur    | ature Rating:   |
| -55.0 de  | grees celsius and 135.0 degrees celsius                                   |
| Environ   | mental Protection:  |
| Corrosic  | on resistant and flame resistant and mildew resistant and water resistant |
| Expand    | ed Inside Diameter:   |
| 0.187 in  | ches  |
| Recove    | red Inside Diameter:  |
| 0.093 in  | ches  |
| Recove    | red Wall Thickness:   |
| Betweer   | 0.015 inches and 0.021 inches   |
| Heat Sh   | rinkage Rating In Percent:  |
| 50.3      |   |
| Min. Te   | nsile Strength (psi):   |
| 1500 po   | unds per square inch  |
| Flexibili | ty:   |
| Semirigi  | d   |
| Color:    |   |
| Yellow    |   |
| Materia   | :   |
| Plastic,  | polyolefin, rt-1800/3, raychem corp                                       |
| Materia   | :   |
| Plastic p | polyolefin  |
| Style De  | esignator:  |
| Shrinkat  | ble   |
| Suppler   | nentary Features:   |
| 2500 sle  | eves supplied on bandolier reel   |
| Dielectr  | ic Material Voltage Rating Per Unit Thickness:                            |
| 500.0 vo  | olts per military /0.001 inch/  |
| Shelf Li  | fe:   |
| N/a       |   |
| Unit Of   | Measure:  |
|           |   |
| Demilita  | arization:  |
| No        |   |
| Fiig:     |   |
| A22500    |   |