Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-229-8771

| Reliability Indicator: |
|--|
| Not established |
| Overall Length: |
| Any acceptable |
| Tempurature Rating: |
| -55.0 degrees celsius and 110.0 degrees celsius |
| Environmental Protection: |
| Corrosion resistant and mildew resistant and water resistant |
| Expanded Inside Diameter: |
| 0.750 inches |
| Recovered Inside Diameter: |
| 0.313 inches |
| Recovered Wall Thickness: |
| 0.065 inches |
| Heat Shrinkage Rating In Percent: |
| 58.3 |
| Min. Tensile Strength (psi): |
| 1500 pounds per square inch |
| Special Features: |
| Meltable inner wall |
| Flexibility: |
| Semirigid |
| Color: |
| White |
| Material: |
| Plastic, polyolefin, mil-i-23053/4, class 1 |
| Material: |
| Plastic polyolefin |
| Style Designator: |
| Shrinkable |
| Dielectric Material Voltage Rating Per Unit Thickness: |
| 500.0 volts per military /0.001 inch/ |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A22500 |
| |