Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-230-1907

N	ot established
0	verall Length:
A	ny acceptable
Te	empurature Rating:
-6	5.0 degrees fahrenheit and 300.0 degrees fahrenheit
Eı	nvironmental Protection:
C	orrosion resistant and flame resistant and mildew resistant and water resistant
E	xpanded Inside Diameter:
0.	375 inches
R	ecovered Inside Diameter:
0.	187 inches
R	ecovered Wall Thickness:
Be	etween 0.015 inches and 0.021 inches
H	eat Shrinkage Rating In Percent:
50).2
М	in. Tensile Strength (psi):
20	000 pounds per square inch
S	pecial Features:
Bl	ack color stripe
FI	exibility:
F١	exible
C	olor:
R	ed
Μ	aterial:
ΡI	astic, polyolefin, mms-809, mcdonnell douglas
Μ	aterial:
ΡI	astic polyolefin
S	tyle Designator:
Sł	nrinkable
Di	ielectric Material Voltage Rating Per Unit Thickness:
50	00.0 volts per military /0.001 inch/
SI	helf Life:
N/	/a
U	nit Of Measure:
D	emilitarization:
N	0
Fi	ig: