NSN 5970-01-230-3711

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-230-3711

T	m	nı	ırat	ure	Ra	tin	u.
15	71 I I	υu	ıιαι	uie	I\a		u.

-55.0 degrees celsius and 125.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Wall Thickness:

0.060 inches after unrestricted recovery

Main Bodylength:

3.000 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.880 inches as supplied

Main Body Large End Inside Diameter:

0.880 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

0.460 inches after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Large end has lip; small end wall thk 0.045 in. After recovery; inside coated with adhesive

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corp

Material:

Plastic, polyolefin, rt-301, raychem corp

Style Designator:

Boot-straight-long

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500