# NSN 5970-01-230-3713

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-230-3713

T		D-	4:
ıem	puratu	re ĸa	tına:

-55.0 degrees celsius and 125.0 degrees celsius

### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

# Main Body Wall Thickness:

0.080 inches after unrestricted recovery

### Main Bodylength:

8.000 inches after unrestricted recovery

# Main Body Small End Inside Diameter:

1.720 inches as supplied

### Main Body Large End Inside Diameter:

1.720 inches as supplied

### Distance From Bottom Of Shoulder To Large End Of Main Body:

0.600 inches after unrestricted recovery

### Min. Tensile Strength (psi):

1500 pounds per square inch

### **Special Features:**

Large end has lip; small end wall thk 0.045 in. After recovery; inside coated with adhesive

# Flexibility:

Semirigid

# Color:

Black

# Material:

Plastic, polyolefin, rt-301, raychem corp

### Material:

Plastic, polyolefin, rt-301, raychem corp

# **Style Designator:**

Boot-straight-long

### **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

### Shelf Life:

N/a

# **Unit Of Measure:**

### **Demilitarization:**

No

# Fiig:

A22500