Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-230-3714

## **Tempurature Rating:** -55.0 degrees celsius and 125.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Main Body Wall Thickness: 0.090 inches after unrestricted recovery Main Bodylength: 8.000 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.970 inches as supplied Main Body Large End Inside Diameter: 1.970 inches as supplied Distance From Bottom Of Shoulder To Large End Of Main Body: 0.600 inches after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Large end has lip; small end wall thk 0.055 in. After recovery; inside coated with adhesive Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp Style Designator: Boot-straight-long **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A22500