

View Online at https://aerobasegroup.com/nsn/5970-01-230-5793

Dielectric Withstanding Voltage In Volts: 200.0 Tempurature Rating: -75.0 degrees celsius and 150.0 degrees celsius Environmental Protection: Water resistant Large End Wall Thickness Of Main Body: 0.070 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.070 inches after unrestricted recovery Main Bodylength: 3.500 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery Min. Tensile Strength (psi): 2.175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Enclargest Diameter: 0.110 inches after unrestricted recovery Min. Tensile Strength (psi): 2.175 pounds per square inch Lip Width: 0.110 inches after unrestricted recovery Enclargest: 0.110 inches after unrestricted recovery Enclargest: 0.110 inches after unrestricted recovery Enclargest: D.110 inches after unrestricted recovery Enclargest: Output D.110 inches after unrestricted recovery Enclargest:
Tempurature Rating: -75.0 degrees celsius and 150.0 degrees celsius Environmental Protection: Water resistant Large End Wall Thickness Of Main Body: 0.070 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.070 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.045 inches after unrestricted recovery Main Bodylength: 3.500 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery
 -75.0 degrees celsius and 150.0 degrees celsius Environmental Protection: Water resistant Large End Wall Thickness Of Main Body: 0.070 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.045 inches after unrestricted recovery Main Bodylength: 3.500 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery
Environmental Protection: Water resistant Large End Wall Thickness Of Main Body: 0.070 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.045 inches after unrestricted recovery Main Bodylength: 3.500 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery
Water resistant Large End Wall Thickness Of Main Body: 0.070 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.045 inches after unrestricted recovery Main Bodylength: 3.500 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2.175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery End Largest Diameter inch Lip Width: 0.110 inches after unrestricted recovery
Large End Wall Thickness Of Main Body: 0.070 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.045 inches after unrestricted recovery Main Bodylength: 3.500 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
0.070 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.045 inches after unrestricted recovery Main Bodylength: 3.500 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
Small End Wall Thickness Of Main Body: 0.045 inches after unrestricted recovery Main Bodylength: 3.500 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
 0.045 inches after unrestricted recovery Main Bodylength: 3.500 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery
Main Bodylength:3.500 inches after unrestricted recoveryMain Body Small End Inside Diameter:1.160 inches as suppliedMain Body Large End Inside Diameter:1.160 inches as suppliedDistance From Top Of Shoulder To Small End Of Main Body:2.240 inches after unrestricted recoveryEnd Largest Diameter:0.810 inches after unrestricted recoveryMin. Tensile Strength (psi):2175 pounds per square inchLip Height:0.120 inches after unrestricted recoveryLip Kidth:0.110 inches after unrestricted recovery
 3.500 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Distonces after unrestricted recovery Flexibility:
Main Body Small End Inside Diameter: 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Fiexibility:
 1.160 inches as supplied Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
 Main Body Large End Inside Diameter: 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
 1.160 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
Distance From Top Of Shoulder To Small End Of Main Body: 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
 2.240 inches after unrestricted recovery End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
End Largest Diameter: 0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
0.810 inches after unrestricted recovery Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
Min. Tensile Strength (psi): 2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
2175 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
0.120 inches after unrestricted recovery Lip Width: 0.110 inches after unrestricted recovery Flexibility:
Lip Width: 0.110 inches after unrestricted recovery Flexibility:
0.110 inches after unrestricted recovery Flexibility:
Flexibility:
•
Semirigid
Semingia
Height:
0.820 inches after unrestricted recovery
Color:
Black
Material:
Plastic, polyvinyl chloride
Material:
Plastic polyvinyl chloride
Style Designator:
Boot-90 degrees
Shelf Life:
N/a
Unit Of Measure:

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500