NSN 5970-01-235-3937

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-235-3937

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 125.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant

Large End Wall Thickness Of Main Body:

0.080 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.080 inches after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

2.110 inches after unrestricted recovery

Distance From Centerline Of Small End To Edge Of Large End:

1.140 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.680 inches as supplied

Main Body Large End Inside Diameter:

1.680 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

0.690 inches after unrestricted recovery

Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Large end has lip

Flexibility:

Flexible

Height:

1.730 inches after unrestricted recovery

Color:

Black

Material:

Plastic, elastomeric polymer, rt-1321, raychem corp

Material:

Plastic, elastomeric polymer, rt-1321, raychem corp

Style Designator:

Boot-90 degrees

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5970-01-235-3937

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500