## NSN 5970-01-235-3940

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5970-01-235-3940     |
|---|
| Tempurature Rating:   |
| -55.0 degrees celsius and 125.0 degrees celsius                   |
| Environmental Protection:   |
| Flame resistant and mildew resistant                              |
| Main Body Wall Thickness:   |
| 0.090 inches after unrestricted recovery                          |
| Main Bodylength:  |
| 3.000 inches after unrestricted recovery                          |
| Main Body Small End Inside Diameter:                              |
| 0.680 inches as supplied  |
| Main Body Large End Inside Diameter:                              |
| 0.940 inches as supplied  |
| Distance From Bottom Of Shoulder To Large End Of Main Body:       |
| 0.460 inches after unrestricted recovery                          |
| Min. Tensile Strength (psi):                                      |
| 1500 pounds per square inch                                       |
| Special Features:   |
| Large end has lip; thk small end tapers to 0.048 in. As recovered |
| Flexibility:  |
| Flexible  |
| Color:  |
| Black   |
| Material:   |
| Plastic, elastomeric polymer, rt-1321, raychem corp               |
| Material:   |
| Plastic, elastomeric polymer, rt-1321, raychem corp               |
| Style Designator:   |
| Boot-straight-long  |
| Dielectric Material Voltage Rating Per Unit Thickness:            |
| 200.0 volts per military /0.001 inch/                             |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

Demilitarization:

No Fiig: A22500