NSN 5970-01-235-8550



Electrical Insulation Sleeving - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5970-01-235-8550 **Reliability Indicator:** Not established **Overall Length:** Any acceptable **Tempurature Rating:** -25.0 degrees celsius and 125.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and water resistant **Expanded Inside Diameter:** 0.500 inches **Recovered Inside Diameter:** 0.250 inches **Recovered Wall Thickness:** Between 0.022 inches and 0.028 inches **Heat Shrinkage Rating In Percent:** 50.0 **End Application:** Mrap - cougar; mrap - m-atv dv178; mrap - cougar cat1 a2 Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Material: plastic, polyolefin, mil-dtl-23053/5, class 3 Flexibility: Flexible Color: White Material: Plastic, polyolefin, mil-dtl-23053/5, class 3 **Style Designator:** Shrinkable **Dielectric Material Voltage Rating Per Unit Thickness:** 500.0 volts per military /0.001 inch/ Shelf Life:

N/a **Unit Of Measure: Demilitarization:** No Fiig: A22500