Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-236-0787

Tempurature Rating	g:
-55.0 degrees celsius	S
<b>Environmental Prot</b>	rection:
Corrosion resistant a	nd flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Wall Thi	ckness:
0.070 inches after u	nrestricted recovery
Main Bodylength:	
5.460 inches after u	nrestricted recovery
Main Body Small E	nd Inside Diameter:
1.160 inches as sup	plied
Main Body Large E	nd Inside Diameter:
1.160 inches as sup	plied
Distance From Bott	om Of Shoulder To Large End Of Main Body:
0.480 inches after u	nrestricted recovery
Min. Tensile Streng	th (psi):
1500 pounds per squ	uare inch
Special Features:	
Large end has lip; in	side coated with adhesive
Flexibility:	
Semirigid	
Color:	
Black	
Material:	
Plastic, polyolefin, r	t-301, raychem corporation or plastic, polyolefin, mpp-262, minnesota mining and maufacturing co
Material:	
Plastic, polyolefin, r	t-301, raychem corporation or plastic, polyolefin, mpp-262, minnesota mining and maufacturing co
Style Designator:	
Boot-straight-long	
Dielectric Material	/oltage Rating Per Unit Thickness:
200.0 volts per milita	ry /0.001 inch/
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	