Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-236-6650

| Reliability Indicator: | |
|--|----|
| Not established | |
| Overall Length: | |
| 1.750 inches | |
| Tempurature Rating: | |
| -55.0 degrees celsius and 135.0 degrees celsius | |
| Environmental Protection: | |
| Corrosion resistant and flame resistant and mildew resistant and water resista | nt |
| Expanded Inside Diameter: | |
| 0.250 inches | |
| Recovered Inside Diameter: | |
| 0.125 inches | |
| Recovered Wall Thickness: | |
| Between 0.015 inches and 0.021 inches | |
| Heat Shrinkage Rating In Percent: | |
| 50.0 | |
| Min. Tensile Strength (psi): | |
| 1500 pounds per square inch | |
| Flexibility: | |
| Semirigid | |
| Color: | |
| Brown | |
| Material: | |
| Plastic, polyolefin, rt-1800/3, raychem corp | |
| Material: | |
| Plastic polyolefin | |
| Style Designator: | |
| Shrinkable | |
| Supplementary Features: | |
| 2500 sleeves supplied on bandolier reel | |
| Dielectric Material Voltage Rating Per Unit Thickness: | |
| 500.0 volts per military /0.001 inch/ | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| - | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A22500 | |