

View Online at <https://aerobasegroup.com/nsn/5970-01-240-5879>

Temperature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Large End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.036 inches after unrestricted recovery and 0.054 inches after unrestricted recovery

Main Bodylength:

4.550 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.450 inches as supplied

Main Body Large End Inside Diameter:

1.720 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

1.650 inches after unrestricted recovery

End Largest Diameter:

Any acceptable as supplied

Min. Tensile Strength (psi):

1200 pounds per square inch

Lip Height:

0.120 inches after unrestricted recovery

Lip Width:

0.065 inches after unrestricted recovery

Special Features:

Molding ports included

Flexibility:

Flexible

Height:

0.840 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin mil-i-81765/1, type 2 or plastic, polyolefin, rt-1304, raychem corp

Material:

Plastic, polyolefin mil-i-81765/1, type 2 or plastic, polyolefin, rt-1304, raychem corp

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500