

View Online at <https://aerobasegroup.com/nsn/5970-01-241-0525>

Dielectric Withstanding Voltage In Volts:

Any acceptable

Tempurature Rating:

-55.0 degrees celsius and 150.0 degrees celsius

Environmental Protection:

Flame resistant

Large End Wall Thickness Of Main Body:

0.060 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.040 inches after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

1.650 inches after unrestricted recovery

Distance From Centerline Of Small End To Edge Of Large End:

0.830 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.710 inches as supplied

Main Body Large End Inside Diameter:

1.220 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

0.710 inches after unrestricted recovery

Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Large end has lip

Flexibility:

Semirigid

Height:

1.220 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin and copper composite, rt-1370, raychem inc

Material:

Plastic, polyolefin and copper composite, rt-1370, raychem inc

Style Designator:

Boot-90 degrees

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500