

View Online at <https://aerobasegroup.com/nsn/5970-01-241-0526>

**Dielectric Withstanding Voltage In Volts:**

Any acceptable

**Tempurature Rating:**

-55.0 degrees celsius and 150.0 degrees celsius

**Environmental Protection:**

Flame resistant

**Large End Wall Thickness Of Main Body:**

0.060 inches after unrestricted recovery

**Small End Wall Thickness Of Main Body:**

0.040 inches after unrestricted recovery

**Distance From Intersecting Centerlines To Edge Of Small End:**

2.000 inches after unrestricted recovery

**Distance From Centerline Of Small End To Edge Of Large End:**

1.020 inches after unrestricted recovery

**Main Body Small End Inside Diameter:**

0.870 inches as supplied

**Main Body Large End Inside Diameter:**

1.420 inches as supplied

**Distance From Top Of Shoulder To Small End Of Main Body:**

0.790 inches after unrestricted recovery

**Angle Between Large End And Small End Centerlines In Deg:**

90.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Special Features:**

Large end has lip

**Flexibility:**

Semirigid

**Height:**

1.500 inches after unrestricted recovery

**Color:**

Black

**Material:**

Plastic, polyolefin and copper composite, rt-1370, raychem inc

**Material:**

Plastic, polyolefin and copper composite, rt-1370, raychem inc

**Style Designator:**

Boot-90 degrees

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500