Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-247-3904

Relia	ability Indicator:
Not e	established
Over	all Length:
Any a	acceptable
Tem	purature Rating:
-25.0) degrees celsius and 125.0 degrees celsius
Envi	ronmental Protection:
Corro	psion resistant and flame resistant and mildew resistant and water resistant
Expa	anded Inside Diameter:
0.37	5 inches
Reco	overed Inside Diameter:
0.187	7 inches
Reco	overed Wall Thickness:
0.02	5 inches
Heat	Shrinkage Rating In Percent:
50.0	
End	Application:
Mrap	- cougar; mrap - m-atv dv178; mrap - cougar cat1 a2
Min.	Tensile Strength (psi):
1500	pounds per square inch
Spec	cial Features:
Plast	ic, polyolefin, mil-dtl-23053/5, class 3
Flexi	ibility:
Flexi	ble
Colo	r:
Black	K
Mate	erial:
Plast	ic, polyolefin, mil-dtl-23053/5, class 3
Style	e Designator:
Shrir	hkable
Diele	ectric Material Voltage Rating Per Unit Thickness:
500.0	0 volts per military /0.001 inch/
Shel	f Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	
Fiig:	
A225	500