

View Online at <https://aerobasegroup.com/nsn/5970-01-250-8064>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-70.0 degrees celsius

**Environmental Protection:**

Flame resistant and mildew resistant

**Main Body Inside Diameter:**

0.820 inches as supplied

**First Branch Inside Diameter:**

0.820 inches as supplied

**Second Branch Inside Diameter:**

0.820 inches as supplied

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

2.480 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.050 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.050 inches after unrestricted recovery

**Second Branch Wall Thickness:**

0.050 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:**

2.480 inches after unrestricted recovery

**Min. Tensile Strength (psi):**

2200 pounds per square inch

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Rubber, synthetic, viton polymer blend, rt-1313, raychem corp

**Material:**

Rubber, synthetic, viton polymer blend, rt-1313, raychem corp

**Style Designator:**

Transition-y

**Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500