## NSN 5970-01-250-8065

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-250-8065 **Reliability Indicator:** Not established **Tempurature Rating:** -70.0 degrees celsius **Environmental Protection:** Flame resistant and mildew resistant **Main Body Inside Diameter:** 0.500 inches as supplied **First Branch Inside Diameter:** 0.500 inches as supplied **Second Branch Inside Diameter:** 0.500 inches as supplied **Distance From Intersecting Centerline Of Main Body To End Of First Branch:** 1.600 inches after unrestricted recovery Main Body Wall Thickness: 0.040 inches after unrestricted recovery First Branch Wall Thickness: 0.040 inches after unrestricted recovery **Second Branch Wall Thickness:** 0.040 inches after unrestricted recovery **Distance From Edge Of Main Body To Intersecting Centerlines:** 1.600 inches after unrestricted recovery Min. Tensile Strength (psi): 2200 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic, viton polymer blend, rt-1313, raychem corp Rubber, synthetic, viton polymer blend, rt-1313, raychem corp **Style Designator:** Transition-y **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5970-01-250-8065

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500