

View Online at https://aerobasegroup.com/nsn/5970-01-251-6805

| Tempurature Rating: |
|--|
| -55.0 degrees celsius |
| Environmental Protection: |
| Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant |
| Large End Wall Thickness Of Main Body: |
| 0.130 inches after unrestricted recovery |
| Small End Wall Thickness Of Main Body: |
| 0.130 inches after unrestricted recovery |
| Distance From Intersecting Centerlines To Edge Of Small End: |
| 3.070 inches after unrestricted recovery |
| Distance From Centerline Of Small End To Edge Of Large End: |
| 1.320 inches after unrestricted recovery |
| Main Body Small End Inside Diameter: |
| 2.040 inches as supplied |
| Main Body Large End Inside Diameter: |
| 2.040 inches as supplied |
| Distance From Top Of Shoulder To Small End Of Main Body: |
| 1.320 inches after unrestricted recovery |
| Angle Between Large End And Small End Centerlines In Deg: |
| 90.0 after unrestricted recovery |
| Min. Tensile Strength (psi): |
| 1200 pounds per square inch |
| Special Features: |
| Inside adhesive coated; large end id of main body has lip |
| Flexibility: |
| Flexible |
| Height: |
| 2.080 inches after unrestricted recovery |
| Color: |
| Black |
| Material: |
| Plastic, polyolefin, rt-1304, raychem corp |
| Material: |
| Plastic, polyolefin, rt-1304, raychem corp |
| Style Designator: |
| Boot-90 degrees |
| Dielectric Material Voltage Rating Per Unit Thickness: |
| 225.0 volts per military /0.001 inch/ |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500