View Online at https://aerobasegroup.com/nsn/5970-01-253-3438

Tempurature Rating: -55.0 degrees celsius and 225.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant Large End Wall Thickness Of Main Body: 0.080 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.045 inches after unrestricted recovery Main Bodylength: 2.000 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.470 inches as supplied Main Body Large End Inside Diameter: 1.470 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: Any acceptable as supplied **End Largest Diameter:** 1.150 inches after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.065 inches after unrestricted recovery **Special Features:** Inside surface coated with adhesive Flexibility: Semirigid Height: 0.960 inches after unrestricted recovery Color: Black Material: Plastic, elastomer, rt-1325, raychem corp Material: Plastic, elastomer, rt-1325, raychem corp Style Designator: Boot-90 degrees **Dielectric Material Voltage Rating Per Unit Thickness:** 300.0 volts per military /0.001 inch/ Shelf Life:

N/a

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A22500