NSN 5970-01-255-7658

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-255-7658

| T | | D = 11 |
|----------|----------|---------|
| ıem | purature | Rating: |

-75.0 degrees celsius and 150.0 degrees celsius

Main Body Wall Thickness:

0.040 inches after unrestricted recovery

Main Bodylength:

2.360 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.420 inches as supplied

Main Body Large End Inside Diameter:

1.420 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

0.860 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

0.790 inches after unrestricted recovery

Min. Tensile Strength (psi):

2175 pounds per square inch

Special Features:

Tab located between exterior small diameter and large diameter with hole 0.080 in. Dia; inside diameter has lip; wall thickness on small end taper to 0.040 in.

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, elastomer, rt-1325, raychem corp

Material:

Plastic, elastomer, rt-1325, raychem corp

Style Designator:

Boot-straight

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500