## NSN 5970-01-262-0167

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-262-0167

_				_		
Т	am	niii	ratii	ro R	≀atin	u.
	CIII	vui	atu	161	\auii	ч.

-55.0 degrees celsius and 135.0 degrees celsius

#### **Environmental Protection:**

Flame resistant and mildew resistant

#### **Main Body Inside Diameter:**

2.910 inches as supplied

#### First Branch Inside Diameter:

1.820 inches as supplied

#### **Second Branch Inside Diameter:**

1.820 inches as supplied

#### **Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

3.700 inches after unrestricted recovery

#### Main Body Wall Thickness:

0.180 inches after unrestricted recovery

#### **First Branch Wall Thickness:**

0.100 inches after unrestricted recovery

#### **Second Branch Wall Thickness:**

0.100 inches after unrestricted recovery

## **Distance From Edge Of Main Body To Intersecting Centerlines:**

3.350 inches after unrestricted recovery

## Angle Between Main Body And Second Branch Centerlines In Deg:

22.5 after unrestricted recovery

#### Min. Tensile Strength (psi):

1500 pounds per square inch

#### **Special Features:**

Inside adhesive coated

## Flexibility:

Flexible

## Color:

Black

#### Material:

Plastic, polyolefin

### Material:

Plastic polyolefin

## Style Designator:

Transition-y

### **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5970-01-262-0167

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500