NSN 5970-01-262-5373

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-262-5373

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Main Body Inside Diameter:

1.290 inches as supplied

First Branch Inside Diameter:

0.840 inches as supplied

Second Branch Inside Diameter:

0.840 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

2.480 inches after unrestricted recovery

Main Body Wall Thickness:

0.050 inches after unrestricted recovery

First Branch Wall Thickness:

0.050 inches after unrestricted recovery

Second Branch Wall Thickness:

0.050 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.480 inches after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

Any acceptable as supplied

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Inside adhesive coated

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin, rt-1316, raychem corp

Material:

Plastic, polyolefin, rt-1316, raychem corp

Style Designator:

Transition-y

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5970-01-262-5373

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500