# NSN 5970-01-263-7184

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-263-7184

## **Tempurature Rating:**

-55.0 degrees celsius and 135.0 degrees celsius

### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and water resistant

### **Main Body Inside Diameter:**

2.190 inches as supplied

### First Branch Inside Diameter:

1.060 inches as supplied

## **Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

3.400 inches after unrestricted recovery

### Main Body Wall Thickness:

0.180 inches after unrestricted recovery

#### First Branch Wall Thickness:

0.100 inches after unrestricted recovery

### **Distance From Edge Of Main Body To Intersecting Centerlines:**

3.760 inches after unrestricted recovery

### Main Bodylength:

7.210 inches after unrestricted recovery

## Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

## Min. Tensile Strength (psi):

1200 pounds per square inch

## Flexibility:

Flexible

## Color:

Black

## Material:

Plastic, polyolefin, mil-i-81765/1, type ii

#### Material:

Plastic, polyolefin, mil-i-81765/1, type ii

## Style Designator:

Transition-45 degrees

### **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

### Shelf Life:

N/a

#### **Unit Of Measure:**

--

## Demilitarization:

No

### Fiig:

A22500