# NSN 5970-01-265-0608

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-265-0608

# **Tempurature Rating:**

-55.0 degrees celsius and 135.0 degrees celsius

#### **Coating Material:**

Adhesive

# Large End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

#### Small End Wall Thickness Of Main Body:

0.040 inches after unrestricted recovery

#### **Distance From Intersecting Centerlines To Edge Of Small End:**

1.810 inches after unrestricted recovery

#### Distance From Centerline Of Small End To Edge Of Large End:

1.020 inches after unrestricted recovery

#### Main Body Small End Inside Diameter:

1.420 inches as supplied

#### **Main Body Large End Inside Diameter:**

1.420 inches as supplied

# Distance From Top Of Shoulder To Small End Of Main Body:

0.590 inches after unrestricted recovery

# Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

# Min. Tensile Strength (psi):

1500 pounds per square inch

#### **Special Features:**

Large end has lip; two injection port holes; tab with 0.080 in. Diameter hole on outer wall angle

# Flexibility:

Semirigid

# Height:

1.500 inches after unrestricted recovery

#### Color:

Black

#### Material:

Plastic, polyolefin, rt-301, raychem corp

# Material:

Plastic, polyolefin, rt-301, raychem corp

# **Style Designator:**

Boot-90 degrees

# **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5970-01-265-0608

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



			on:	

No

Fiig:

A22500