NSN 5970-01-268-2442

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-268-2442

Tempurature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Large End Wall Thickness Of Main Body:

0.060 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

Main Bodylength:

1.750 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.250 inches as supplied

Main Body Large End Inside Diameter:

0.760 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

0.860 inches after unrestricted recovery

End Largest Diameter:

0.440 inches after unrestricted recovery

Min. Tensile Strength (psi):

2000 pounds per square inch

Lip Height:

0.120 inches after unrestricted recovery

Lip Width:

0.040 inches after unrestricted recovery

Flexibility:

Semirigid

Height:

0.640 inches after unrestricted recovery

Color:

Black

Material:

Plastic, elastomer, rt-1325, raychem corp

Material:

Plastic, elastomer, rt-1325, raychem corp

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5970-01-268-2442

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500