NSN 5970-01-268-2443

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-268-2443

Tempurature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Large End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

Main Bodylength:

2.650 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.300 inches as supplied

Main Body Large End Inside Diameter:

1.030 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

1.150 inches after unrestricted recovery

End Largest Diameter:

0.660 inches after unrestricted recovery

Min. Tensile Strength (psi):

2000 pounds per square inch

Lip Height:

0.120 inches after unrestricted recovery

Lip Width:

0.040 inches after unrestricted recovery

Flexibility:

Semirigid

Height:

0.710 inches as supplied

Color:

Black

Material:

Plastic, elastomer, rt-1325, raychem corp

Material:

Plastic, elastomer, rt-1325, raychem corp

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5970-01-268-2443

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500