NSN 5970-01-273-7800

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-273-7800 **Reliability Indicator:** Established **Tempurature Rating:** -55.0 degrees celsius and 121.0 degrees celsius **Main Body Inside Diameter:** 0.520 inches as supplied First Branch Inside Diameter: 0.260 inches as supplied **Second Branch Inside Diameter:** 0.260 inches as supplied **Distance From Intersecting Centerline Of Main Body To End Of First Branch:** 0.760 inches after unrestricted recovery Main Body Wall Thickness: 0.060 inches after unrestricted recovery **First Branch Wall Thickness:** 0.040 inches after unrestricted recovery **Second Branch Wall Thickness:** 0.040 inches after unrestricted recovery **Distance From Edge Of Main Body To Intersecting Centerlines:** 0.880 inches after unrestricted recovery Angle Between Main Body And Second Branch Centerlines In Deg: 22.5 after unrestricted recovery Min. Tensile Strength (psi): 1200 pounds per square inch **Special Features:** Adhesive, raychem corp., s-10488 Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp **Style Designator:** Transition-y **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a

--

Unit Of Measure:

NSN 5970-01-273-7800

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



			ati	

No

Fiig:

A22500