Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-273-7801

Tempurature Rating: -55.0 degrees celsius and 121.0 degrees celsius Main Body Inside Diameter: 2.190 inches as supplied First Branch Inside Diameter: 0.520 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 2.830 inches after unrestricted recovery Main Body Wall Thickness: 0.180 inches after unrestricted recovery **First Branch Wall Thickness:** 0.060 inches after unrestricted recovery **Distance From Edge Of Main Body To Intersecting Centerlines:** 3.280 inches after unrestricted recovery Main Bodylength: 7.280 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1200 pounds per square inch **Special Features:** Adhesive, raychem corp., s-1048 Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp Style Designator: Transition-45 degrees **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A22500