# NSN 5970-01-276-7754

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-276-7754

### **Tempurature Rating:**

-55.0 degrees celsius and 121.0 degrees celsius

### **Main Body Inside Diameter:**

1.520 inches as supplied

#### First Branch Inside Diameter:

1.060 inches as supplied

### **Second Branch Inside Diameter:**

1.060 inches as supplied

### Distance From Intersecting Centerline Of Main Body To End Of First Branch:

3.220 inches after unrestricted recovery

### Main Body Wall Thickness:

0.120 inches after unrestricted recovery

#### First Branch Wall Thickness:

0.100 inches after unrestricted recovery

#### **Second Branch Wall Thickness:**

0.100 inches after unrestricted recovery

### **Distance From Edge Of Main Body To Intersecting Centerlines:**

2.580 inches after unrestricted recovery

# Angle Between Main Body And Second Branch Centerlines In Deg:

22.5 after unrestricted recovery

# Min. Tensile Strength (psi):

1200 pounds per square inch

# Special Features:

Adhesive, raychem corp., s-10488

# Flexibility:

Semirigid

# Color:

Black

#### Material:

Plastic, polyolefin, rt-301, raychem corp

### Material:

Plastic, polyolefin, rt-301, raychem corp

### **Style Designator:**

Transition-y

### **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

### Shelf Life:

N/a

# **Unit Of Measure:**

--

### **Demilitarization:**

No

# NSN 5970-01-276-7754

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500