NSN 5970-01-278-1318

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-278-1318

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant

Large End Wall Thickness Of Main Body:

0.060 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

Main Bodylength:

4.880 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.950 inches as supplied

Main Body Large End Inside Diameter:

0.950 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

3.900 inches after unrestricted recovery

End Largest Diameter:

0.600 inches after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Lip Height:

0.120 inches after unrestricted recovery

Lip Width:

0.040 inches after unrestricted recovery

Special Features:

Inside adhesive coating, s-1048, raychem corp

Flexibility:

Semirigid

Height:

0.780 inches after unrestricted recovery

Color:

Black

Material:

Plastic, elastomer, rt-1325, raychem corp

Material:

Plastic, elastomer, rt-1325, raychem corp

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

300.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5970-01-278-1318

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	2 †1	n	
_		ш	ıιa	114	au	VII	١.

No

Fiig:

A22500