

View Online at https://aerobasegroup.com/nsn/5970-01-282-5571

Environmental Protection: Corrosion resistant and flame resistant and mildew resistant Large End Wall Thickness Of Main Body: 0.110 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.040 inches after unrestricted recovery **Distance From Intersecting Centerlines To Edge Of Small End:** 1.560 inches after unrestricted recovery Distance From Centerline Of Small End To Edge Of Large End: 0.660 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.460 inches as supplied Main Body Large End Inside Diameter: 0.940 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 0.370 inches after unrestricted recovery Angle Between Large End And Small End Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Includes molding ports Flexibility: Semirigid Height: 1.300 inches after unrestricted recovery Color: Black Material: Plastic, elastomer, rt-1325, raychem corp Material: Plastic, elastomer, rt-1325, raychem corp Style Designator: Boot-90 degrees **Dielectric Material Voltage Rating Per Unit Thickness:** 300.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

NSN 5970-01-282-5571

Special Purpose Electrical Insulation Sleeving - Page 2 of 2

Fiig: A22500

