NSN 5970-01-282-9950

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-282-9950

Tempurature Rating:

-55.0 degrees celsius

Main Body Inside Diameter:

1.520 inches as supplied

First Branch Inside Diameter:

1.060 inches as supplied

Second Branch Inside Diameter:

1.060 inches as supplied

Third Branch Inside Diameter:

1.060 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

2.900 inches after unrestricted recovery

Main Body Wall Thickness:

0.120 inches after unrestricted recovery

First Branch Wall Thickness:

0.070 inches after unrestricted recovery

Second Branch Wall Thickness:

0.070 inches after unrestricted recovery

Third Branch Wall Thickness:

0.070 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.420 inches after unrestricted recovery

Main Bodylength:

5.320 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

Any acceptable after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin, rt-1304, raychem corp

Material:

Plastic, polyolefin, rt-1304, raychem corp

Style Designator:

Transition-1 to 3 cables

Dielectric Material Voltage Rating Per Unit Thickness:

225.0 volts per military /0.001 inch/

Shelf Life:

N/a

NSN 5970-01-282-9950

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A22500