Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-285-3353

Reliability	Indicator:
Not establis	shed
Overall Le	ngth:
4.000 inche	25
Tempuratu	ire Rating:
-55.0 degre	es celsius and 175.0 degrees celsius
Environme	ental Protection:
Flame resis	stant and mildew resistant and solvent resistant and water resistant
Expanded	Inside Diameter:
0.250 inche	95
Recovered	Inside Diameter:
0.125 inche	25
Recovered	Wall Thickness:
0.012 inche	25
Heat Shrin	kage Rating In Percent:
50.0	
Min. Tensi	le Strength (psi):
5000 pound	ds per square inch
Flexibility:	
Semirigid	
Color:	
Natural	
Material:	
Plastic, pol	lyvinylidene fluoride, ams 3632
Style Desig	gnator:
Shrinkable	
Dielectric I	Material Voltage Rating Per Unit Thickness:
900.0 volts	per military /0.001 inch/
Specificati	on Data:
81343-ams	3632 professional/industrial association specification
Specificati	on Or Standard:
0.250in size	9
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	
Fiig:	
A22500	