

View Online at <https://aerobasegroup.com/nsn/5970-01-285-5720>

Tempurature Rating:

-55.0 degrees celsius and 250.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Main Body Inside Diameter:

0.720 inches as supplied

First Branch Inside Diameter:

0.460 inches as supplied

Second Branch Inside Diameter:

0.460 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.600 inches after unrestricted recovery

Main Body Wall Thickness:

0.040 inches after unrestricted recovery

First Branch Wall Thickness:

0.040 inches after unrestricted recovery

Second Branch Wall Thickness:

0.040 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.600 inches after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

45.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Inside adhesive coated

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin, rt-1316, raychem corp

Material:

Plastic, polyolefin, rt-1316, raychem corp

Style Designator:

Transition-y

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500