Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-288-9685

Tempurature Rating	
-55.0 degrees celsius	
Environmental Prote	ection:
Corrosion resistant ar	nd flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Wall Thio	kness:
0.060 inches after un	restricted recovery
Main Bodylength:	
1.500 inches after un	restricted recovery
Main Body Small En	d Inside Diameter:
0.890 inches as supp	lied
Main Body Large En	d Inside Diameter:
0.890 inches as supp	lied
Distance From Botto	om Of Shoulder To Large End Of Main Body:
0.830 inches after un	restricted recovery
Distance From Top	Of Shoulder To Small End Of Main Body:
0.390 inches after un	restricted recovery
Min. Tensile Strengt	h (psi):
1200 pounds per squ	are inch
Special Features:	
Tab located between	exterior small diameter and large diameter with hole 0.080 in. Dia; wall thickness on small end tapers to 0.020 in.;
inside adhesive coate	d
Flexibility:	
Flexible	
Color:	
Black	
Material:	
Plastic, polyolefin, rt-1	304, raychem corp
Material:	
Plastic, polyolefin, rt-1	304, raychem corp
Style Designator:	
Boot-straight	
Dielectric Material V	oltage Rating Per Unit Thickness:
225.0 volts per militar	y /0.001 inch/
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	
Fiig:	
A22500	