# NSN 5970-01-291-7495

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-291-7495

# **Tempurature Rating:**

-55.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

# **Main Body Inside Diameter:**

1.520 inches as supplied

#### First Branch Inside Diameter:

0.760 inches as supplied

#### **Second Branch Inside Diameter:**

0.760 inches as supplied

#### **Third Branch Inside Diameter:**

0.760 inches as supplied

#### **Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

2.900 inches as supplied

#### Main Body Wall Thickness:

0.120 inches as supplied

#### First Branch Wall Thickness:

0.070 inches as supplied

# **Second Branch Wall Thickness:**

0.070 inches as supplied

# **Third Branch Wall Thickness:**

0.070 inches as supplied

#### **Distance From Edge Of Main Body To Intersecting Centerlines:**

2.420 inches as supplied

# Main Bodylength:

5.320 inches as supplied

# Angle Between Main Body And First Branch Centerlines In Deg:

30.0 after unrestricted recovery

#### Min. Tensile Strength (psi):

1200 pounds per square inch

#### **Special Features:**

Inside coated with adhesive

# Flexibility:

Flexible

# Color:

Black

# Material:

Plastic, polyolefin, rt 1304, raychem corp

# Material:

Plastic, polyolefin, rt 1304, raychem corp

# Style Designator:

Transition-1 to 3 cables

# NSN 5970-01-291-7495

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A22500