

View Online at <https://aerobasegroup.com/nsn/5970-01-291-9363>

Temperature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Inside Diameter:

2.190 inches as supplied

First Branch Inside Diameter:

1.060 inches as supplied

Second Branch Inside Diameter:

1.060 inches as supplied

Third Branch Inside Diameter:

1.060 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

4.060 inches after unrestricted recovery

Main Body Wall Thickness:

0.180 inches after unrestricted recovery

First Branch Wall Thickness:

0.120 inches after unrestricted recovery

Second Branch Wall Thickness:

0.120 inches after unrestricted recovery

Third Branch Wall Thickness:

0.120 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

3.500 inches after unrestricted recovery

Main Bodylength:

7.560 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

30.0 after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpf-666, 3m co

Material:

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpf-666, 3m co

Style Designator:

Transition-1 to 3 cables

Dielectric Material Voltage Rating Per Unit Thickness:

225.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500