## NSN 5970-01-293-1650

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-293-1650

view Offiline at https://aerobasegroup.com/hsh/5570-01-255-1000
Reliability Indicator:
Established
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Distance From Intersecting Centerlines To Edge Of Small End:
2.100 inches after unrestricted recovery
Distance From Centerline Of Small End To Edge Of Large End:
1.000 inches after unrestricted recovery
Main Body Wall Thickness:
0.040 inches after unrestricted recovery
Main Body Small End Inside Diameter:
1.350 inches as supplied
Main Body Large End Inside Diameter:
2.310 inches after unrestricted recovery
End Application:
Solid state receiver/digital moving target ind. (ssr-dmti)
Min. Tensile Strength (psi):
1200 pounds per square inch
Special Features:
Entire inner surface coated with thermo adhesive; subminiature; end entry; overexpanded
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, polyolefin, rt-301, raychem corp
Material:
Plastic, polyolefin, rt-301, raychem corp
Style Designator:
Boot-rectangular-90 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A22500