View Online at https://aerobasegroup.com/nsn/5970-01-295-8861

## Special Purpose Electrical Insulation Sleeving - Page 1 of 1 **Reliability Indicator:** Established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Distance From Intersecting Centerlines To Edge Of Small End: 1.210 inches after unrestricted recovery Distance From Centerline Of Small End To Edge Of Large End: 0.730 inches after unrestricted recovery Main Body Wall Thickness: 0.040 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.750 inches as supplied Main Body Large End Inside Diameter: 1.110 inches after unrestricted recovery Min. Tensile Strength (psi): 1200 pounds per square inch **Special Features:** Entire inner surface coated with thermo adhesive; subminiature; end entry; overexpanded Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp Style Designator: Boot-rectangular-90 degrees **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: **Demilitarization:** Yes - demil/mli Fiig: A22500