

View Online at <https://aerobasegroup.com/nsn/5970-01-297-5189>

Tempurature Rating:

-55.0 degrees celsius and 125.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant and water resistant

Large End Wall Thickness Of Main Body:

0.060 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

Main Bodylength:

2.750 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.880 inches as supplied

Main Body Large End Inside Diameter:

0.880 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

2.060 inches after unrestricted recovery

End Largest Diameter:

0.570 inches after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Lip Height:

0.120 inches after unrestricted recovery

Lip Width:

0.040 inches after unrestricted recovery

Flexibility:

Semirigid

Height:

0.730 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, poloyolefin, mil-i-87165/1, type i

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, poloyolefin, mil-i-87165/1, type i

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500