Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-298-9270

## **Tempurature Rating:** -55.0 degrees celsius and 135.0 degrees celsius Large End Wall Thickness Of Main Body: 0.040 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.040 inches after unrestricted recovery **Distance From Intersecting Centerlines To Edge Of Small End:** 0.680 inches after unrestricted recovery Distance From Centerline Of Small End To Edge Of Large End: 0.610 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.700 inches as supplied Main Body Large End Inside Diameter: 0.700 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 0.170 inches after unrestricted recovery Angle Between Large End And Small End Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 1200 pounds per square inch Flexibility: Flexible Height: 0.790 inches after unrestricted recovery Color: Black Material: Plastic, polyolefin, mil-i-81765/1, type ii Material: Plastic, polyolefin, mil-i-81765/1, type ii Style Designator: Boot-90 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A22500