## NSN 5970-01-305-0944

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-305-0944

## **Tempurature Rating:**

-75.0 degrees celsius and 250.0 degrees celsius

#### **Main Body Inside Diameter:**

2.190 inches as supplied

#### First Branch Inside Diameter:

1.060 inches as supplied

#### **Second Branch Inside Diameter:**

1.060 inches as supplied

#### **Third Branch Inside Diameter:**

1.060 inches as supplied

#### **Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

4.060 inches after unrestricted recovery

#### Main Body Wall Thickness:

0.180 inches after unrestricted recovery

#### First Branch Wall Thickness:

0.120 inches after unrestricted recovery

#### **Second Branch Wall Thickness:**

0.120 inches after unrestricted recovery

#### **Third Branch Wall Thickness:**

0.120 inches after unrestricted recovery

## **Distance From Edge Of Main Body To Intersecting Centerlines:**

3.500 inches after unrestricted recovery

#### Main Bodylength:

7.560 inches after unrestricted recovery

## Angle Between Main Body And First Branch Centerlines In Deg:

30.0 after unrestricted recovery

## Flexibility:

Flexible

## Color:

Black

#### Material:

Rubber, silicone, rt-602, rayclad tubes inc

## Material:

Rubber, silicone, rt-602, rayclad tubes inc

### **Style Designator:**

Transition-1 to 3 cables

## **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5970-01-305-0944

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500