Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-309-8907

-55.0 degrees celsius and 225.0 degrees celsius Environmental Protection: Corrosion resistant and flame resistant and mildew resistant Distance From Centerline Of Main Body To End Of First Branch: 7.800 inches after unrestricted recovery Main Body Inside Diameter: 2.190 inches as supplied First Branch Inside Diameter: 1.060 inches as supplied Main Body Wall Thickness:

Tempurature Rating:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.100 inches after unrestricted recovery

Main Bodylength:

7.800 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, elastomer, rt-1325, raychem corp

Material:

Plastic, elastomer, rt-1325, raychem corp

Style Designator:

Transition-t

Dielectric Material Voltage Rating Per Unit Thickness:

300.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500