Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-312-5499

Reliability Indicator:	
Not established	
Overall Length:	
Any acceptable	
Tempurature Rating:	
-25.0 degrees celsius and	d 125.0 degrees celsius
Environmental Protectio	-
Corrosion resistant and fl	ame resistant and mildew resistant and water resistant
Expanded Inside Diame	eter:
1.000 inches	
Recovered Inside Diame	eter:
0.500 inches	
Recovered Wall Thickne	ess:
0.035 inches	
Heat Shrinkage Rating I	In Percent:
50.0	
End Application:	
Mrap - m-atv dv178; mra	ap - cougar; mrap - cougar cat1 a2
Min. Tensile Strength (p	osi):
1500 pounds per square	inch
Special Features:	
Plastic, polyolefin, mil-dt	tl-23053/5, class 3
Flexibility:	
Flexible	
Color:	
White	
Material:	
Plastic, polyolefin, mil-dt	tl-23053/5, class 3
Style Designator:	
Shrinkable	
Dielectric Material Volta	age Rating Per Unit Thickness:
500.0 volts per military /0	.001 inch/
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	