## NSN 5970-01-324-0841

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-324-0841

Main	Body	/ Inside	Diameter:

1.520 inches after unrestricted recovery

First Branch Inside Diameter:

0.380 inches after unrestricted recovery

**Second Branch Inside Diameter:** 

0.070 inches after unrestricted recovery

**Third Branch Inside Diameter:** 

0.380 inches after unrestricted recovery

**Fourth Branch Inside Diameter:** 

0.380 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of Second Branch:

2.830 inches after unrestricted recovery

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:** 

2.570 inches after unrestricted recovery

Main Body Wall Thickness:

0.120 inches after unrestricted recovery

First Branch Wall Thickness:

0.070 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 as supplied

Angle Between Main Body And Second Branch Centerlines In Deg:

15.0 as supplied

Min. Tensile Strength (psi):

900 pounds per square inch

**Style Designator:** 

Transition-1 to 4 cables

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A22500