## NSN 5970-01-327-3248

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-327-3248

View Online at https://aerobasegroup.com/nsn/5970-01-327-3248
Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius and 225.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Inside Diameter:
1.000 inches as supplied
First Branch Inside Diameter:
0.500 inches as supplied
Second Branch Inside Diameter:
0.500 inches as supplied
Third Branch Inside Diameter:
0.500 inches as supplied
Main Body Wall Thickness:
0.060 inches as supplied
First Branch Wall Thickness:
0.060 inches after unrestricted recovery
Second Branch Wall Thickness:
0.060 inches after unrestricted recovery
Third Branch Wall Thickness:
0.060 inches as supplied
Main Bodylength:
4.250 inches after unrestricted recovery
Min. Tensile Strength (psi):
1200 pounds per square inch
Flexibility:
Flexible
Color:
Black
Material:
Plastic, polyolefin, rt-1304, raychem corp
Material:
Plastic, polyolefin, rt-1304, raychem corp
Style Designator:
Transition, 1 to 3 cables, parallel
Dielectric Material Voltage Rating Per Unit Thickness:
225.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5970-01-327-3248

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



em			

No

Fiig:

A22500